

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF
A PORTION OF THE EAST BOUNDARY,
AND A PORTION OF THE SUBDIVISIONAL LINES,
THE CORRECTIVE RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF SECTION 22,
THE SURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 10, 11, 13, 15, 25, AND 26,

IN

TOWNSHIP 3 SOUTH, RANGE 8 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Baugh, Supervisory Cadastral Surveyor

and

Daniel T. Gillins, Survey Technician

Under Special Instructions dated and approved **November 6, 2006**, which provided for the surveys included under Group Number **1036**, and Assignment Instructions dated **November 6, 2006**.

Survey Commenced, **November 16, 2006**
Survey Completed, **September 13, 2008**

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

ORIGINAL

FIELD NOTES

OF

THE DEPENDENT RESURVEY OF
A PORTION OF THE EAST BOUNDARY,
AND A PORTION OF THE SUBDIVISIONAL LINES,
THE CORRECTIVE RESURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES,
AND THE SUBDIVISION OF SECTION 22,
THE SURVEY OF
A PORTION OF THE SUBDIVISIONAL LINES,

AND

THE SUBDIVISION OF SECTIONS 10, 11, 13, 15, 25, AND 26,

IN

TOWNSHIP 3 SOUTH, RANGE 8 WEST,

OF THE SALT LAKE MERIDIAN
IN THE STATE OF UTAH

EXECUTED BY

Ronald K. Baugh, Supervisory Cadastral Surveyor

and

Daniel T. Gillins, Survey Technician

Under Special Instructions dated and approved **November 6, 2006**, which provided for the surveys included under Group Number **1036**, and Assignment Instructions dated **November 6, 2006**.

Survey Commenced, **November 16, 2006**
Survey Completed, **September 13, 2008**

INDEX DIAGRAM

Township 3 South, Range 8 West.

6	5	4	3	2	1
7	8	9	23 22 10	19 17 11	11 12
18	17	16	22 21 15	16 15 14	10 11 13 6 33
19	20	21	20 29 19 22 29	35 24 23	33 34 24 5
30	29	28	28 27 27	14 13 26	9 7 25 4
31	32	33	34	12 35	7 36 3

The Corrective Resurvey of the Subdivision of Section 22.....	Page 29
The Subdivision of Section 10.....	Page 36
The Subdivision of Section 11.....	Page 38
The Subdivision of Section 13.....	Page 41
The Subdivision of Section 15.....	Page 43
The Subdivision of Section 25.....	Page 45
The Subdivision of Section 26.....	Page 45
Survey of Iosepa Cemetery in Section 22.....	Page 47

TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

The following field notes are those of the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines, the corrective resurvey of a portion of the subdivisional lines and the subdivision of section 22, the survey of a portion of the subdivisional lines, and the subdivision of sections 10, 11, 13, 15, 25, and 26, in Township 3 South, Range 8 West, Salt Lake Meridian, Utah.

History of Surveys

Surveyed by	Retr. Or Resurveyed by
SOUTH BOUNDARY	
All J. Gorlinski	1871
EAST BOUNDARY	
All J. Gorlinski	1871
Portion	R.K. Baugh 2004
WEST BOUNDARY	
All J. Gorlinski	1871
NORTH BOUNDARY	
All J. Gorlinski	1871
Portion	A.J. Stookey 1906
Portion	R.K. Baugh 2004
Portion	R.K. Baugh & D.T. Gillins 2007
SUBDIVISION	
Portion J. Gorlinski	1871
Portion	R.K. Baugh 1985
Portion	R.K. Baugh 2004
PRIVATE SURVEY	

R.E. Caldwell executed a survey of the townsite of Iosepa as per his Townsite plat recorded in the Tooele County Recorder's Office on August 5, 1908.

TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH

The survey was executed in accordance with the specifications set forth in the Manual of Surveying Instructions, 1973, and the Special Instructions for Group No. 1036, dated November 6, 2006.

The direction of the lines was determined by references to true meridians, established by Global Positioning System (GPS) utilizing Real-Time Kinematic (RTK) techniques throughout the survey. The positional accuracy of this survey complies with the Standards and Guidelines for Cadastral Surveys Using Global Positioning System Methods, dated May 9, 2001, Version 1.0. Trimble model 5800 GPS receivers were used for field collection. Cadastral Automated Plat Drafting (CAPD) software was the primary software utilized for the project calculations.

Preliminary to the resurvey, the lines of the prior surveys were retraced and search was made for all corners and other calls of record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions based on the official record. The retracement data was thoroughly verified and only the true line field notes are given herein.

Cadastral Control Network was derived from GPS static observations, post processed by the National Geodetic Survey, Online Positioning User Service (OPUS), utilizing Continuously Operating Reference Stations (CORS): KENNECOTT1UT2005 CORS ARP, SALT LAKE CITY CORS ARP, and MIDVALE CORS ARP.

The geographic position of the corner of sections 26, 27, 34, and 35, T. 3 S., R. 8 W., as determined by direct RTK methods from the National Geodetic Survey OPUS solution, is as follows:

Latitude: 40°31'15.397" N.,
Longitude: 112°43'28.452" W., N.A.D. 1983,
Network Accuracy = 0.200 meter at 95% confidence.
N.A.V.D. 1988 Elevation: 4696 ft.

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Dependent Resurvey of a Portion of the East Boundary,
Township 3 South, Range 8 West, Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by J. Gorlinski
in 1871.

Beginning at the corner of Townships 3 and 4 South, Ranges 7 and 8 West, determined at record bearing and distance from the remaining 1871 bearing tree:

A cedar, 14 inches diameter, bears S. 43°15' E., 100 links distance, with illegible scribe marks on an open blaze.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

T 3 S	
R 8 W	R 7 W
<u>S 36</u>	<u>S 31</u>
S 1	S 6
T 4 S	
2007	

Corner is located 11 links south of the center of a small creek, drains west; and is 13 ft. beneath a north draining corrugated steel pipeline, 24 inches diameter, on top of a steel rail bridge.

N. 0°00.5' E., between sections 31 and 36.

39.893 The 1/4 section corner of sections 31, and 36, determined at record distance from the 1871 bearing trees:

A cedar, 14 inches diameter, bears N. 77° E., 19 links distance, with illegible scribe marks on an open blaze.
(Record: N. 78° E.)

A cedar stump, 11 inches diameter, bears N. 28° W., 14 links distance. (Record: N. 25° W.)

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

	T 3 S	
R 8 W		R 7 W
	1/4	
S 36		S 31
	2007	

Corner is located on east edge of a concrete and rock canal, 8 links wide, 4 links deep, drains north.

N. 0°19.0' E., beginning new measurement.

- 39.516 Point for the corner of sections 25, 30, 31, and 36, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

	T 3 S	
R 8 W		R 7 W
S 25		S 30
S 36		S 31
	2007	

Set a steel fence post 1 link east of the aluminum post.

Corner is located on north facing, rocky slope.

N. 0°19.0' E., between sections 25 and 30.

- 39.516 Point for the 1/4 section corner of sections 25, and 30, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

	T 3 S	
R 8 W		R 7 W
	1/4	
S 25		S 30
	2007	

Set a steel fence post alongside the aluminum post.

From this point, a cobblestone 18 X 14 X 5 inches, plainly marked with a "4", lying face up in a scattered mound of stone, bears N. 86°56.4' E., 8.264 chains distance. The "4" marked on this stone is different than other stones marked "1/4" that were

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

found during this survey. In addition, if this stone is the original corner, record distances to nearby creeks to the north and south do not fit. Since the origin of this stone could not be determined, bury the stone in place, face down.

- 79.032** The corner of sections 19, 24, 25, and 30, monumented with a quartzite stone, 12 X 12 X 5 inches, firmly set, plainly marked with 2 notches on south edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

T 3 S	
R 8 W	R 7 W
S 24	S 19
S 25	S 30

2007

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0°25.9' E., between sections 19 and 24.

- 39.328** Point for the 1/4 section corner of section 24 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T 3 S	
R 8 W	R 7 W
1/4	
S 24	

2008

- 39.408** Point for the 1/4 section corner of sections 19 and 24, at proportionate distance, there is no remaining evidence of the original corner. This point will now function as the 1/4 section corner of section 19 only, Township 3 South, Range 7 West.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T 3 S	
R 8 W	R 7 W
	1/4
	S 19

2007

DEPENDENT RESURVEY OF A PORTION OF THE EAST BOUNDARY,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set a steel fence post alongside the aluminum post.

- 78.816** The corner of sections 13, 18, 19, and 24, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, marked as described in the official record of the 2004 resurvey; with a mound of stone, 3 ft. base, 1 1/2 links west of corner.

This corner will now function as the section corner of sections 18 and 19 only, Township 3 South, Range 7 West. Change the marks on the aluminum cap by removing "S13" and adding "2008".

Reestablishment of the Survey Executed by J. Gorlinski
in 1871, and the Resurvey Executed by R.K. Baugh in 2004

N. 0°37.2' E., along the west boundary of section 18.

- 0.512** Point for the closing corner of sections 13 and 24, hereinafter described.

- 40.016** The 1/4 section corner of sections 13 and 18, monumented with an aluminum post, 2 1/2 inches diameter, projecting 4 inches above the ground, with aluminum cap marked as described in the official record of the 2004 resurvey, with a mound of stone 3 ft. base, 2 ft. high, 2 links west of corner.
-

N. 0°08.0' W., beginning new measurement.

- 19.990** Point for the N 1/16 section corner of sections 13 and 18.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

N 1/16
S 13 | S 18
2008

Set a steel fence post along the north side of the aluminum post.

Corner is located on east facing slope.

- 39.980** The corner of sections 7, 12, 13, and 18, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, in a mound of stone, 2 ft. base, to top of aluminum cap marked as described in the official record of the 2004 resurvey.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Dependent Resurvey of a Portion of the Subdivisional Lines,
Township 3 South, Range 8 West, Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by J. Gorlinski
in 1871.

From the corner of sections 25, 30, 31, and 36, on the east
boundary of the township, hereinbefore described.

N. 89°55.7' W., between sections 25 and 36.

- 40.069 Point for the 1/4 section corner of sections 25 and 36, at
proportionate distance, there is no remaining evidence of the
original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12
inches in the ground, in a mound of stone, 3 ft. base, to top of
aluminum cap marked:

T 3 S R 8 W
S 25
1/4 —————
S 36
2007

Set a steel fence post alongside the aluminum post.

- 80.138 The corner of sections 25, 26, 35, and 36, monumented with a
cobble stone, 12 X 9 X 5 inches, firmly set in a scattered mound
of stone, projecting 5 inches above the ground, plainly marked
with 1 notch on south edge and 1 notch on east edge; with a
steel fence post 4 links NW of corner.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22
inches in the ground, in a mound of stone, 3 ft. base, to top of
aluminum cap marked:

T 3 S R 8 W
S 26 S 25
S 35 S 36
2006

Bury the marked stone, inverted, alongside the aluminum post.

N. 0°22.5' E., between sections 25 and 26.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

20.000 Point for the S 1/16 section corner of sections 25 and 26.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

S 1/16
S 26 | S 25
2007

Set a steel fence post alongside the aluminum post.

40.000 Point for the 1/4 section corner of sections 25 and 26, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with aluminum cap marked:

T 3 S R 8 W
1/4
S 26 | S 25
2007

Raise a mound of stone, 1 ft. base, 1 ft. high, east of corner.

Set a steel fence post alongside the aluminum post.

Corner is located on a steep, east facing slope.

80.000 Point for the corner of sections 23, 24, 25, and 26, determined by three point control, longitudinally at proportionate distance, and latitudinally at record distance northing (80.00 chains) from the corner of sections 25, 26, 35, and 36, there is no remaining evidence of the original corner. This point will now function as the corner of sections 25 and 26 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 8 inches in the ground to bedrock, in a mound of stone, 4 ft. base, to top of aluminum cap marked:

T 3 S R 8 W
S 23
S 26 | S 25
2007

Set a steel fence post alongside the aluminum post.

Corner is located on steep, rocky, west facing slope.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

From the corner of sections 19, 24, 25, and 30, on the east boundary of the township, hereinbefore described.

N. $89^{\circ}45.2'$ W., along the north boundary of section 25.

38.973 Point for the $1/4$ section corner of section 24 only.

Set an aluminum post, 30 inches long, 2 $1/2$ inches diameter, 26 inches in the ground, with aluminum cap marked:

T 3 S R 8 W
 $1/4$ S 24

2008

40.152 The $1/4$ section corner of sections 24 and 25, monumented with a sandstone, 16 X 10 X 4 inches, firmly set, marked $1/4$, broken in two pieces; from which the 1871 bearing trees:

A stump hole, bears N. $3^{\circ}38'$ E., 13.4 links distance, with an uprooted cedar lying alongside with dim scribe marks " $1/4$ S" visible. (Record: N. $2^{\circ}15'$ W., 14 links)

A cedar, 6 inches diameter, bears S. $56^{\circ}30'$ W., 64 links distance, with scribe marks " $1/4$ S" visible on a partially healed blaze. (Record: 68 links)

This corner will now function as the $1/4$ section corner of section 25 only.

At the corner point

Set an aluminum post, 30 inches long, 2 $1/2$ inches diameter, 18 inches in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T 3 S R 8 W

$1/4$ S 25
2006

Bury the marked stone alongside the aluminum post.

Set a steel fence post 2 links south of the aluminum post.

Corner is located in bottom of a winding, easterly drainage.

N. $88^{\circ}42.1'$ W., beginning new measurement.

38.831 Point for the closing corner of sections 23 and 24, hereinafter described.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

- 39.894 The corner of sections 25 and 26, only.
-

From the corner of sections 7, 12, 13, and 18, on the east boundary of the township, hereinbefore described.

S. 89°44.1' W., between sections 12 and 13.

- 20.019 Point for the E 1/16 section corner of sections 12 and 13.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

	S 12
E 1/16	_____
	S 13
	2008

Set a steel fence post alongside the aluminum post.

- 40.038 The 1/4 section corner of sections 12 and 13, monumented with a limestone 28 X 15 X 6 inches, loosely set, dimly marked 1/4 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

	T 3 S R 8 W
	S 12
1/4	_____
	S 13
	2007

Bury the marked stone, inverted, alongside the aluminum post.

N. 88°59.2' W., beginning new measurement.

- 19.922 Point for the W 1/16 section corner of sections 12 and 13, not monumented.

- 39.844 The corner of sections 11, 12, 13, and 14, monumented with a limestone, 23 X 14 X 7 inches, firmly set, plainly marked with 4 notches on south edge and 1 notch on east edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T 3 S R 8 W

S 11	S 12
S 14	S 13

2007

Bury the marked stone, inverted, alongside the aluminum post.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, 2 links west of corner.

South, between sections 13 and 14.

20.000 Point for the N 1/16 section corner of sections 13 and 14.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

N 1/16	
S 14	S 13
2007	

Set a steel fence post alongside the aluminum post.

40.000 Point for the 1/4 section corner of sections 13 and 14, at record bearing and distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

T 3 S R 8 W	
1/4	
S 14	S 13
2007	

Raise a mound of stone, 2 ft. base, 2 links west of corner.

Corner is located on very steep, NW facing slope.

From the corner of sections 11, 12, 13, and 14.

N. 0°19.3' E., between sections 11 and 12.

20.001 Point for the S 1/16 section corner of sections 11 and 12.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

S 1/16
S 11 | S 12
2007

- 40.002 The 1/4 section corner of sections 11, and 12, monumented with a cobble stone 12 X 9 X 5 inches, firmly set, projecting 1 inch above the ground, plainly marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T 3 S R 8 W
1/4
S 11 | S 12
2007

Bury the marked stone, inverted, alongside the aluminum post.

Corner is located on a very gentle, north facing, grassy slope.

N. 0°11.7' E., beginning new measurement.

- 19.986 Point for the N 1/16 section corner of sections 11 and 12, not monumented.
- 39.972 The corner of sections 1, 2, 11, and 12, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 4 inches above the ground, with aluminum cap marked as described in the official record of the 2004 resurvey, with a mound of stone, 2 ft. base, 2 links west of corner.

From the corner of sections 25, 26, 35, and 36.

S. 89°38.0' W., between sections 26 and 35.

- 19.998 Point for the E 1/16 section corner of sections 26 and 35, not monumented.
- 39.996 Point for the 1/4 section corner of sections 26 and 35, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 12 inches in the ground, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T 3 S R 8 W
S 26
1/4 —————
S 35
2006

Set a steel fence post alongside the aluminum post.

- 79.992 The corner of sections 26, 27, 34, and 35, monumented with a quartzite stone, 22 X 12 X 8 inches, loosely set, plainly marked with 1 notch on south edge and 2 notches on east edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 3 S R 8 W

S 27 | S 26
S 34 | S 35

2006

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located just north of the center line of a drainage, 15 links wide, 7.5 links deep, drains west.

N. 0°19.0' E., between sections 26 and 27.

- 40.068 The 1/4 section corner of sections 26 and 27, monumented with a limestone 13 X 9 X 5 inches, loosely set, marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

T 3 S R 8 W
1/4
S 27 | S 26
2006

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Corner is located just south of a two-track dirt road, bears E-

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

W.

N. 1°01.8' E., beginning new measurement.

- 39.995 The corner of sections 22, 23, 26, and 27, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with aluminum cap marked as described in the official record of the 1985 resurvey.
-

From the corner of sections 25 and 26 only.

S. 89°40.0' W., along the north boundary of section 26.

- 19.890 Point for the E 1/16 section corner of section 26 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

E 1/16 S 26
2007

Set a steel fence post alongside the aluminum post.

Corner is located on south facing slope, 38 links north of a drainage, course SW.

- 38.937 Point for the 1/4 section corner of section 23 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

T 3 S R 8 W
1/4 S 23

2008

- 39.780 Point for the 1/4 section corner of sections 23 and 26, at proportionate distance, there is no remaining evidence of the original corner. This point will now function as the 1/4 section corner of section 26 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 3 S R 8 W

1/4 S 26
2007

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set a steel fence post alongside the aluminum post.

79.560 The corner of sections 22, 23, 26, and 27.

From the corner of sections 14, 15, 22, and 23, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 10 inches above a mound of stone, 3 feet base, 6 inches high, with aluminum cap marked as described in the official record of the 1985 resurvey.

This corner will now function as the corner of sections 15 and 22 only. Change the marks on the aluminum cap by removing "S23" and adding "2008".

N. 0°23.5' E., along the east boundary of section 15.

38.681 Point for the 1/4 section corner of sections 14 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

T 3 S R 8 W	
	1/4
	S 14
	2008

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, 2 links east of corner.

Corner is located on steep, west facing slope.

39.428 The 1/4 section corner of sections 14 and 15, monumented with a limestone, 17 X 14 X 12 inches, loosely set, projecting 8 inches above the ground, plainly marked 1/4 on west face. This corner will now function as the 1/4 section corner of section 15 only.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 2 ft. base, 6 inches high, to top of aluminum cap marked:

T 3 S R 8 W	
	1/4
S 15	
	2006

Deposit the marked stone, inverted, at the bottom of the mound of stone.

N. 0°19.4' E., beginning new measurement.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

- 40.010** The corner of sections 10, 11, 14, and 15, monumented with a cobble stone, 17 X 7 X 6 inches, loosely set, plainly marked with 4 notches on south edge and 2 notches on east edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with aluminum cap marked:

T 3 S R 8 W	
S 10	S 11
S 15	S 14

2006

Bury the marked stone, inverted, alongside the aluminum post.

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, 3 links west of corner.

Set a steel fence post alongside the aluminum post.

From the corner of sections 11, 12, 13, and 14.

S. 89°43.8' W., between sections 11 and 14.

- 19.606** Point for the E 1/16 section corner of section 11 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 2 inches in the ground, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

E 1/16	S 11
--------	------

2007

Corner is located on the saddle of a ridge, bears NE-SW.

- 39.212** The 1/4 section corner of sections 11 and 14, monumented with a limestone, 32 X 16 X 7 inches, set on top of a limestone outcrop, plainly marked 1/4 on north face. This corner will now function as the 1/4 section corner of section 11 only.

At the corner point

Set a rebar, 8 inches long, 3/4 inch diameter, 3 inches in cement bond, into a drill hole on solid limestone outcrop, with an aluminum cap, 3 1/4 inches diameter, marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T 3 S R 8 W
1/4 S 11

2007

Raise a mound of stone, 3 ft. base, 2 ft. high, north of corner.

Deposit the marked stone, inverted, at the bottom of the mound of stone.

Corner is located on steep, west facing slope.

N. 88°39.7' W., beginning new measurement.

0.788 Point for the 1/4 section corner of sections 14 only.

Cement a rebar, 6 inches long, 3/4 inch diameter, 2 inches in cement bond, into a drill hole on solid limestone outcrop, with an aluminum cap, 3 1/4 inches diameter, marked:

T 3 S R 8 W

1/4 S 14
2008

40.420 The corner of sections 10, 11, 14, and 15.

N. 0°14.6' E., between sections 10 and 11.

20.005 Point for the S 1/16 section corner of sections 10 and 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

S 1/16

S 10 | S 11

2007

Set a steel fence post alongside the aluminum post.

40.010 The 1/4 section corner of sections 10 and 11, monumented with a limestone 10 X 8 X 3 inches, loosely set in a scattered mound of stone, plainly marked 1/4 on west face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 21 inches in the ground, in a mound of stone, 3 feet base, to top of aluminum cap marked:

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T 3 S R 8 W
1/4
S 10 | S 11
2006

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 0°10.1' W., beginning new measurement.

20.002 Point for the N 1/16 section corner of sections 10 and 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, in a collar of stone, 1 ft. base, with aluminum cap marked:

N 1/16
S 10 | S 11
2007

Set a steel fence post alongside the aluminum post.

Corner is located on west facing slope in an open grassy area.

40.004 Point for the corner of sections 2, 3, 10, and 11, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 3 S R 8 W
S 3 | S 2
S 10 | S 11
2007

Raise a mound of stone, 3 ft. base, 1 1/2 ft. high, west of corner.

Set a steel fence post alongside the aluminum post.

Corner is located on a gradual west facing slope, in grassy area, 55 links south of a barbed wire fence extending east and west.

From this point the corner of sections 2, 3, 34, and 35, on the

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

north boundary of the township, bears N. 0°00.6' E., 79.572 chains distance, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 3 inches above the ground, with aluminum cap marked as described in the official record of the 2007 resurvey of the south boundary of Township 2 South, Range 8 West, Group 1053, with a mound of stone, 3 ft. base, 1 ft. high, north of corner.

The control line was fully retraced, and no evidence of the 1/4 section corner of sections 2 and 3 was found.

From the corner of sections 1, 2, 11, and 12.

N. 89°25.4' W., between sections 2 and 11.

19.979 Point for the E 1/16 section corner of sections 2 and 11, not monumented.

39.958 Point for the 1/4 section corner of sections 2 and 11, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 20 inches in the ground, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

	T 3 S R 8 W
	S 2
1/4	_____
	S 11
	2007

Set a steel fence post alongside the aluminum post.

79.916 The corner of sections 2, 3, 10, and 11.

From the 1/4 section corner of sections 21 and 22, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 2 inches above the ground, with aluminum cap marked as described in the official record of the 1985 resurvey; with a steel fence post alongside.

N. 0°01.9' W., between sections 21 and 22.

39.989 The corner of sections 15, 16, 21, and 22, at the center of a mound of stone under a barbed wire fence extending east and west. This position is harmoniously related to existing original corners, and is accepted as the best available evidence of the original corner position.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

inches in the ground, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

T 3 S R 8 W

S 16	S 15
S 21	S 22

2006

From this corner the 1/4 section corner of sections 17 and 20 bears N. 89°41.4' W., 120.266 chains distance, monumented with a limestone, 16 X 10 X 6 inches, loosely set, plainly marked 1/4 on north face, with a 6 inch square railroad tie set 3 links north of corner.

At this corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T 3 S R 8 W

S 17

1/4 —————

S 20

2006

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

Note: This corner was tied to in an effort to verify the position of the corner of sections 15, 16, 21, and 22.

From the 1/4 section corner of sections 15 and 22, monumented with an aluminum post, 2 1/2 inches diameter, firmly set, projecting 6 inches above the ground, with aluminum cap marked as described in the official record of the 1985 resurvey.

Corner is located at a fence corner with barbed wire fences extending east, west, and south.

N. 89°44.8' W., between sections 15 and 22.

21.498 Point for the W 1/16 section corner of sections 15 and 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap remarked:

S 15
W 1/16 —————
S 22
2007

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set a steel fence post alongside the aluminum post.

Corner is located 2 links south of a barbed wire fence extending east and west.

42.996 The corner of sections 15, 16, 21, and 22.

N. $0^{\circ}24.6'$ E., between sections 15 and 16.

20.015 Point for the S $1/16$ section corner of sections 15 and 16.

Set an aluminum post, 30 inches long, 2 $1/2$ inches diameter, over a steel fence post, 6 ft. long, driven 5 ft. 8 inches in the ground, with aluminum cap marked:

S $1/16$
S 16 | S 15
2007

Corner is located in a swamp.

40.030 Point for the $1/4$ section corner of sections 15 and 16, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 $1/2$ inches diameter, 27 inches in the ground, with aluminum cap marked:

T 3 S R 8 W
 $1/4$
S 16 | S 15
2006

Set a steel fence post alongside the aluminum post.

80.060 The corner of sections 9, 10, 15, and 16, monumented with a sandstone, 12 X 8 X 6 inches, firmly set, projecting 4 inches above the ground, marked with 4 notches on south edge and 3 notches on east edge.

At the corner point

Set an aluminum post, 30 inches long, 2 $1/2$ inches diameter, 28 inches in the ground, with aluminum cap marked:

T 3 S R 8 W
S 9 | S 10
S 16 | S 15
2006

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Bury the marked stone, inverted, alongside the aluminum post.

Corner is located in a swamp, approximately 3 chains south of a ditch, 15 links wide, course east.

From the corner of sections 10, 11, 14, and 15.

N. 89°13.4' W., between sections 10 and 15.

20.034 Point for the E 1/16 section corner of sections 10 and 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

$$\begin{array}{r} \text{S } 10 \\ \hline \text{E } 1/16 \text{ ---} \\ \text{S } 15 \\ 2007 \end{array}$$

Set a steel fence post alongside the aluminum post.

Corner is located on a gentle west facing slope, in grassy area.

40.068 True point for the 1/4 section corner of sections 10 and 15, at proportionate distance, falls on the west edge of State Road 196, where it is unsuitable for monumentation; there is no remaining evidence of the original corner.

41.318 Point selected for the witness 1/4 section corner of sections 10 and 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

$$\begin{array}{r} \text{T } 3 \text{ S } \text{R } 8 \text{ W} \\ \text{S } 10 \\ 1/4 \text{ ---} \rightarrow \text{WC} \\ \text{S } 15 \\ 2006 \end{array}$$

Set a steel fence post alongside the aluminum post.

Corner is located 10 links east of a barbed wire fence extending north and south.

80.136 The corner of sections 9, 10, 15, and 16.

N. 0°16.1' E., between sections 9 and 10.

19.950 Point for the S 1/16 section corner of sections 9 and 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

inches in the ground, with aluminum cap marked:

T 3 S R 8 W
S 1/16

S 9 | S 10

2006

Set a steel fence post alongside the aluminum post.

- 39.900 Point for the 1/4 section corner of sections 9 and 10, at proportionate distance, there is no remaining evidence of the original corner.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

T 3 S R 8 W
1/4

S 9 | S 10

2006

Set a steel fence post alongside the aluminum post.

- 79.800 The corner of sections 3, 4, 9, and 10, monumented with a sandstone, 10 X 10 X 10 inches, firmly set, projecting 8 inches above a scattered mound of stone, marked with 5 notches on south edge and 3 notches on east edge.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

T 3 S R 8 W

S 4	S 3
S 9	S 10

2006

Bury the marked stone, inverted, alongside the aluminum post.

Raise a mound of stone, 2 ft. base, 1 1/2 ft. high, 3 links west of corner.

Set a steel fence post alongside the aluminum post.

From the corner of sections 2, 3, 10, and 11.

S. 89°44.3' W., between sections 3 and 10.

DEPENDENT RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

- 19.959 Point for the E 1/16 section corner of sections 3 and 10, not monumented.
- 39.918 The 1/4 section corner of sections 3 and 10, monumented with a limestone 12 X 8 X 6 inches, loosely set, plainly marked 1/4 on north face.

At the corner point

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

T 3 S R 8 W
S 3
1/4 —————
S 10
2006

Bury the marked stone, inverted, alongside the aluminum post.

Set a steel fence post alongside the aluminum post.

N. 88°29.3' W., beginning new measurement.

- 19.943 Point for the W 1/16 section corner of sections 3 and 10.
- Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

S 3
W 1/16 —————
S 10
2007

Raise a mound of stone, 2 ft. base, 1 ft. high, north of corner.

Set a steel fence post alongside the aluminum post.

Corner is located on flat grassy area, 1.70 chains west of a dirt road, bears N-S.

- 39.886 The corner of sections 3, 4, 9, and 10.

Corrective Resurvey of a Portion of the Subdivisional Lines,
Township 3 South, Range 8 West, Salt Lake Meridian, Utah.

Reestablishment of the Survey Executed by J. Gorlinski in 1871
and Correction of the Resurvey Executed by R.K. Baugh in 1985.

Note. For the following three reasons, correction of the 1985 resurvey executed by R.K. Baugh is necessary in order to restore

CORRECTIVE RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

the corners to their original 1871 locations by the best available evidence:

1. During the 1985 resurvey, the east boundary of section 22 was recorded as N. 2°28' E., 80.12 chains distance, and the north boundary of the NE 1/4 of section 22 was recorded as N. 89°38' W., 40.23 chains distance, due to a blunder in measurement to the corner of sections 14, 15, 22, and 23. Actually, the east boundary of section 22 is N. 0°20.2' E., 80.030 chains distance, and the north boundary of the NE 1/4 of section 22 is N. 89°34.8' W., 37.229 chains distance.
2. The original 1871 1/4 section corner of sections 22 and 23 was not found during the 1985 resurvey. The said corner was then reestablished at midpoint on the incorrect east boundary of section 22 as stated in no. 1. During this survey, the original 1871 1/4 section corner of sections 22 and 23 is found and herein described. This original corner will control. The 1985 monument set at midpoint is removed and no longer controls in establishing other corner points.
3. During the 1985 resurvey, the original 1871 corner of sections 21, 22, 27, and 28 was not found. The said corner was then reestablished by double proportion method. Mr. Matt Clark, Deputy County Surveyor of Tooele County, found evidence of the original 1871 position of the said corner which also conforms with record ties to existing road monuments set during R.E. Caldwell's 1908 survey of the townsite of Iosepa. This evidence is herein described and will control in reestablishing the original 1871 position of the said corner. The 1985 monument set by proportionate distance is removed and no longer controls in establishing other corner points.

From the corner of sections 22, 23, 26, and 27.

N. 0°25.2' E., along the east boundary of section 22.

20.006 Point for the S 1/16 section corner of section 22 only.

From this point, a monument set for the S 1/16 section corner of sections 22 and 23, an aluminum post, 30 inches long, 2 1/2 inches diameter, with aluminum cap, as described in the official record of the 1985 resurvey, bears S.89°47.1'E., 0.724 chains distance.

This monument is removed and reset 28 inches in the ground at this point for the S 1/16 section corner of section 22 only, with aluminum cap remarked:

T 3 S R 8 W
S 1/16

S 22

CORRECTIVE RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Corner is located on south facing, sandy slope.

- 38.711 Point for the 1/4 section corner of section 23 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

T 3 S R 8 W	
1/4	
S 23	
2007	

- 40.012 The original 1871 1/4 section corner of sections 22 and 23, monumented with a stationary limestone, 16 X 8 X 4 ft. above the ground, plainly marked 1/4 on west face.

This point will now function as the 1/4 section corner of section 22 only.

At the corner point

Set a rebar, 8 inches long, 3/4 inch diameter, 4 inches in cement bond, into a drill hole on the markings on the stationary limestone, with an aluminum cap, 3 1/4 inches diameter, marked:

T 3 S R 8 W	
1/4	
S 22	
2007	

From this corner, a monument set at proportionate distance for the 1/4 section corner of sections 22 and 23, an aluminum post, 30 inches long, 2 1/2 inches diameter, with aluminum cap and a mound of stone to the west, as described in the official record of the 1985 resurvey, bears S.89°47.0'E., 1.449 chains distance. Remove this monument and destroy the mound of stone.

N. 0°15.1' E., beginning new measurement.

- 38.699 Point for the closing corner of sections 14 and 23, hereinafter described.

- 40.018 The corner of sections 15 and 22, hereinbefore described.
-

CORRECTIVE RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

From the corner of sections 27, 28, 33, and 34, monumented with an aluminum post, 2 1/2 inches diameter, firmly set in a mound of stone, 2 ft. base, 4 inches high to top of aluminum cap marked as described in the official record of the 1985 resurvey.

N. 0°34.7' E., between sections 27 and 28.

- 40.281** Point for the 1/4 section corner of sections 27 and 28, at proportionate distance, there is no remaining evidence of the original 1871 corner.

From this point, a monument set for the 1/4 section corner of sections 27 and 28, an aluminum post, 30 inches long, 2 1/2 inches diameter, with aluminum cap and a mound of stone to the west, as described in the official record of the 1985 resurvey, bears S. 56°59.4' W., 0.172 chains distance. Destroy the mound of stone.

This monument is removed and reset 28 inches in the ground at this point for the 1/4 section corner of sections 27 and 28, with aluminum cap remarked:

T 3 S R 8 W	
1/4	
S 28	S 27
2008	

Raise a mound of stone, 4 ft. base, 2 ft. high, 2 links west of corner.

Set a steel fence post alongside the aluminum post.

Corner is located 2.15 chains south of center line of a dirt road, bears E-W.

- 80.562** The corner of sections 21, 22, 27, and 28, determined at the center of an 18 inch diameter pit. This position is accepted as the best available evidence of the original 1871 corner position since it is also harmoniously related with short ties to existing road monuments set during the Iosepa Townsite Survey executed by R.E. Caldwell, dated 1908:

A limestone, 5 inches square, firmly set flush with ground at the intersection of the center lines of planned roads Honolulu Avenue and Napela Street, bears S. 0°39.6' W., 6.996 chains distance (27.98 rods), plainly marked with a cross on top, in a collar of stone. (Caldwell Record: South, 28 rods)

A limestone, 5 inches square, firmly set flush with ground at the intersection of the planned north right-of-way line of Kula Avenue with the planned center line of Napela Street,

CORRECTIVE RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

bears S. $0^{\circ}37.0'$ W., 19.493 chains distance (77.97 rods),
plainly marked with a cross on top, in a collar of stone.
(Caldwell Record: South, 78 rods)

From this point, a monument set at proportionate distance for
the corner of sections 21, 22, 27, and 28, an aluminum post, 30
inches long, 2 1/2 inches diameter, with aluminum cap and a
mound of stone to the west, as described in the official record
of the 1985 resurvey, bears S. $50^{\circ}03.4'$ W., 0.308 chains
distance. Destroy the mound of stone.

This monument is removed and reset 28 inches in the pit, which
is thereafter filled with dirt and stone, at this point for the
corner of sections 21, 22, 27, and 28, with aluminum cap
remarked:

T 3 S R 8 W

S 21	S 22
S 28	S 27

2008

Set a steel fence post alongside the aluminum post.

Corner is located 4.5 links west of an ancient rock foundation
wall, and is at the center of Iosepa's town square, Imilani
Square.

From this corner, the 1/4 section corner of sections 20 and 29,
monumented with an aluminum post, 2 1/2 inches diameter, firmly
set flush with ground, with aluminum cap marked as described in
the official record of the 1985 resurvey, bears N. $89^{\circ}40.3'$ W.,
121.521 chains distance.

From the corner of sections 22, 23, 26, and 27.

N. $89^{\circ}37.7'$ W., between sections 22 and 27.

19.976 Point for the E 1/16 section corner of sections 22 and 27.

From this point, a monument set for the E 1/16 section corner of
sections 22 and 27, an aluminum post, 30 inches long, 2 1/2
inches diameter, in a mound of stone, with aluminum cap, as
described in the official record of the 1985 resurvey, bears
S. $49^{\circ}33.7'$ W., 0.070 chains distance. Destroy the mound of
stone.

This monument is removed and reset 24 inches in the ground at
this point for the E 1/16 section corner of sections 22 and 27,
in a mound of stone, 3 ft. base, to top of aluminum cap
remarked:

CORRECTIVE RESURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T 3 S R 8 W
S 22
E 1/16 —————
S 27
2007

39.952 Point for the 1/4 section corner of sections 22 and 27, at proportionate distance, falls on fill from private garbage dump; there is no remaining evidence of the original 1871 corner, not monumented.

79.904 The corner of sections 21, 22, 27, and 28.

N. 0°13.3' E., between sections 21 and 22.

39.983 The 1/4 section corner of sections 21 and 22.

From the corner of sections 15 and 22 only.

N. 89°34.8' W., between sections 15 and 22.

37.229 The 1/4 section corner of sections 15 and 22.

Corrective Resurvey of the Subdivision of Section 22,
Township 3 South, Range 8 West, Salt Lake Meridian, Utah.

Correction of the Subdivision Executed by
R.K. Baugh in 1985.

Due to the corrections of the exterior boundaries of section 22 hereinbefore described, it is now necessary to also correct the 1985 subdivision of section 22.

From the point for the 1/4 section corner of sections 22 and 27.

N. 2°16.8' E., on the N-S center line of section 22.

20.012 Point for the center S 1/16 section corner of section 22.

From this point, a monument set for the center S 1/16 section corner of section 22, an aluminum post, 30 inches long, 2 1/2 inches diameter, with aluminum cap and mound of stone to the west, as described in the official record of the 1985 resurvey, bears S.61°01.1'W., 0.095 chains distance. Destroy the mound of stone.

This monument is removed and reset 28 inches in the ground at this point for the center S 1/16 section corner of section 22, with aluminum cap remarked:

CORRECTIVE RESURVEY OF THE SUBDIVISION OF SECTION 22,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

C
S 1/16 | S 22
C
2007

Set a steel fence post alongside the aluminum post.

Corner is located in bottom of small drainage, course.

30.018 Point for the center-N-S 1/64 section corner of section 22.

From this point, a monument set for the center-N-S 1/64 section corner of section 22, an aluminum post, 30 inches long, 2 1/2 inches diameter, with aluminum cap, as described in the official record of the 1985 resurvey, bears S.73°15.8'W., 0.071 chains distance.

This monument is removed and reset 26 inches in the ground at this point for the center-N-S 1/64 section corner of section 22, with aluminum cap remarked:

S 22
C-N-S
1/64
2008

From this point, a fence corner for barbed wire fences extending east and north bears S. 48°00.7' W., 0.109 chains distance.

36.225 Intersect the east boundary of the Iosepa Cemetery.

37.576 Intersect the north boundary of the Iosepa Cemetery.

40.024 Point for the center 1/4 section corner of section 22 at the intersection with the E-W center line of section.

From this point, a monument set for the center 1/4 section corner of section 22, an aluminum post, 30 inches long, 2 1/2 inches diameter, with aluminum cap and wood post alongside, as described in the official record of the 1985 resurvey, bears N.84°41.8'W., 0.054 chains distance. Remove the wood post.

This monument is removed and reset 29 inches in the ground at this point for the center 1/4 section corner of section 22, with aluminum cap remarked:

T 3 S R 8 W

C 1/4
S 22

2007

CORRECTIVE RESURVEY OF THE SUBDIVISION OF SECTION 22,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Reset the wood post, 8 inches square, alongside the aluminum post.

Corner is located at a fence corner with barbed wire fences extending east and south.

From this corner, the NW corner of Iosepa Cemetery, bears S. $54^{\circ}07.9'$ W., 4.060 chains distance.

80.106 The 1/4 section corner of sections 15 and 22.

From the 1/4 section corner of section 22 only.

N. $89^{\circ}38.9'$ W., on the E-W center line of section 22.

19.325 Point for the center E 1/16 section corner of section 22.

From this point, a monument set for the center E 1/16 section corner of section 22, an aluminum post, 30 inches long, 2 1/2 inches diameter, in a mound of stone, with aluminum cap, as described in the official record of the 1985 resurvey, bears N. $89^{\circ}44.5'E.$, 0.694 chains distance. Destroy the mound of stone.

This monument is removed and reset 27 inches in the ground at this point for the center E 1/16 section corner of section 22, in a mound of stone, 3 ft. base, to top of aluminum cap remarked:

T 3 S R 8 W
E 1/16
C ————— C
S 22
2007

Corner is located on level bench.

36.235 Point for the C-W-W-W-E 1/1024 section corner of section 22.

From this point, a monument set for the C-W-W-W-E 1/1024 section corner of section 22, an aluminum post, 30 inches long, 2 1/2 inches diameter, with aluminum cap, as described in the official record of the 1985 resurvey, bears N. $83^{\circ}08.6'E.$, 0.040 chains distance.

This monument is removed and reset 26 inches in the ground at this point for the C-W-W-W-E 1/1024 section corner of section 22, with aluminum cap remarked:

S 22
1/1024
2008

From this point, a fence corner for barbed wire fences extending

CORRECTIVE RESURVEY OF THE SUBDIVISION OF SECTION 22,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

west and south bears N. 69°55.7' E., 6 links distance.

38.650 The center 1/4 section corner of section 22.

80.035 The 1/4 section corner of sections 21 and 22.

From the E 1/16 section corner of sections 22 and 27.

N. 1°21.0' E., on the N-S center line of the SE 1/4 of section 22.

20.006 Point for the SE 1/16 section corner of section 22, at the intersection with the E-W center line of the SE 1/4 of section.

From this point, a monument set for the SE 1/16 section corner of section 22, an aluminum post, 30 inches long, 2 1/2 inches diameter, with aluminum cap, as described in the official record of the 1985 resurvey, bears S.85°45.2'E., 0.321 chains distance.

This monument is removed and reset 22 inches in the ground at this point for the SE 1/16 section corner of section 22, in a mound of stone, 3 ft. base, to top of aluminum cap remarked:

T 3 S R 8 W
SE 1/16
S 22
2007

40.012 The center E 1/16 section corner of section 22.

From the S 1/16 section corner of section 22 only.

N. 89°38.2' W., on the E-W center line of the SE 1/4 of section 22.

19.651 The SE 1/16 section corner of section 22.

39.302 The center S 1/16 section corner of section 22.

From the center-N-S 1/64 section corner of section 22.

S. 89°38.5' E., on the E-W center line of the NW 1/4 of the SE 1/4 of section 22.

2.436 Point for the C-W-W-NW-SE 1/1024 section corner of section 22.

From this point, a monument set for the C-W-W-NW-SE 1/1024 section corner of section 22, an aluminum post, 30 inches long, 2 1/2 inches diameter, with aluminum cap, as described in the official record of the 1985 resurvey, bears S.10°26.4'E., 0.020 chains distance.

CORRECTIVE RESURVEY OF THE SUBDIVISION OF SECTION 22,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

This monument is removed and reset 27 inches in the ground at this point for the C-W-W-NW-SE 1/1024 section corner of section 22, with aluminum cap remarked:

S 22
1/1024
2008

From this point, a fence corner for barbed wire fences extending west and north bears S. 48°12.0' E., 6 links distance.

N. 2°09.8' E., on the N-S center line of the W 1/2 of the NW 1/4 of the NW 1/4 of the SE 1/4 of section 22.

10.005 The C-W-W-W-E 1/1024 section corner of section 22.

Survey of a Portion of the Subdivisional Lines,
Township 3 South, Range 8 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 13 and 14.

South, between sections 13 and 14.

40.000 Point for the corner of sections 13, 14, 23, and 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 10 inches in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T 3 S R 8 W

S 14	S 13
S 23	S 24

2008

Set a steel fence post along the south side of the aluminum post.

Corner is located on NW facing slope.

East, between sections 13 and 24.

39.556 Point for the 1/4 section corner of section 13 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, in a mound of stone, 2 1/2 ft. base, to top of aluminum cap marked:

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

T 3 S R 8 W
1/4 S 13

2007

Corner is located on SE facing slope.

40.000 Point for the 1/4 section corner of section 24 only.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T 3 S R 8 W

1/4 S 24
2008

Corner is located on SE facing slope.

79.556 The point for the closing corner of sections 13 and 24, at intersection with the east boundary of the township.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T 3 S
R 8 W R 7 W

C S 13 |
C S 24 | S 18

2008

Raise a mound of stone, 2 1/2 ft. base, 1 1/2 ft. high, 2 links west of corner.

From the corner of sections 13, 14, 23, and 24.

South, between sections 23 and 24.

40.000 Point for the 1/4 section corner of sections 23 and 24.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, with aluminum cap marked:

T 3 S R 8 W
1/4
S 23 | S 24

2008

Set a steel fence post along the south side of the aluminum

SURVEY OF A PORTION OF THE SUBDIVISIONAL LINES,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

post.

Corner is located on east facing slope.

- 78.272** Point for the closing corner of sections 23 and 24, at intersection with the north boundary of section 25.

Set a rebar, 8 inches long, 3/4 inch diameter, 4 inches in cement bond, into a drill hole on solid limestone outcrop, with an aluminum cap, 3 1/4 inches diameter, marked:

T 3 S R 8 W	
C	C
S 23	S 24
S 25	
2008	

From the corner of sections 13, 14, 23, and 24.

West, between sections 14 and 23.

- 40.000** Point for the 1/4 section corner of sections 14 and 23.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T 3 S R 8 W	
S 14	
1/4	_____
S 23	
2008	

Corner is located on east facing slope.

From this point, United States Geological Survey triangulation station "SALT", set in 1955, bears S. 24°14.3' E., 13.453 chains distance, a brass tablet, 3 1/2 inches diameter, cemented into a solid limestone outcrop, marked SALT 1955. This station is located 45 links east of the top of Salt Mountain.

- 80.140** Point for the closing corner of sections 14 and 23, at intersection with the east boundary of section 22.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 18 inches in the ground to bedrock, in a mound of stone, 3 ft. base, to top of aluminum cap marked:

T 3 S R 8 W					
S 22	<table style="border-collapse: collapse; margin: 0 auto;"> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 14</td> <td style="padding: 0 5px;">C</td> </tr> <tr> <td style="border-right: 1px solid black; padding: 0 5px;">S 23</td> <td style="padding: 0 5px;">C</td> </tr> </table>	S 14	C	S 23	C
S 14	C				
S 23	C				
2008					

THE SUBDIVISION OF SECTION 10,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

The Subdivision of Section 10,
Township 3 South, Range 8 West, Salt Lake Meridian, Utah.

From the true point for the 1/4 section corner of sections 10 and 15.

N. 0°08.3' E., on the N-S center line of section 10.

19.979 Point for the center S 1/16 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

C
S 1/16 | S 10
C
2007

Set a steel fence post alongside the aluminum post.

39.958 Point for the center 1/4 section corner of section 10 at the intersection with the E-W center line of section.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 3 S R 8 W
C 1/4 S 10
2007

Set a steel fence post alongside the aluminum post.

Corner is located on flat area in scattered greasewood, 23 links SE of a drainage, course SW.

59.624 Point for the center N 1/16 section corner of section 10, not monumented.

79.290 The 1/4 section corner of sections 3 and 10.

From the 1/4 section corner of sections 10 and 11.

N. 89°18.2' W., on the E-W center line of section 10.

20.069 Point for the center E 1/16 section corner of section 10.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, in a collar of stone, 1 ft. base, with aluminum cap marked:

THE SUBDIVISION OF SECTION 10,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

E 1/16
C ————— C
S 10
2007

Set a steel fence post alongside the aluminum post.

Corner is located on a gentle west slope in grassy area, 38 links south of a drainage, course NW.

40.138 The center 1/4 section corner of section 10.

80.110 The 1/4 section corner of sections 9 and 10.

From the center E 1/16 section corner of section 10.

N. 0°01.0' W., on the N-S center line of the NE 1/4 of section 10.

19.834 Point for the NE 1/16 section corner of section 10, at the intersection with the E-W center line of the NE 1/4 of section.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

NE 1/16 S 10
2007

Set a steel fence post alongside the aluminum post.

Corner is located on a gentle west slope, 1 chain west of a barbed wire fence extending north and south.

39.668 The point for the E 1/16 section corner of sections 3 and 10.

From the N 1/16 section corner of sections 10 and 11.

N. 89°46.8' W., on the E-W center line of the NE 1/4 of section 10.

20.013 The NE 1/16 section corner of section 10.

40.026 The point for the center N 1/16 section corner of section 10.

From the E 1/16 section corner of sections 10 and 15.

N. 0°11.5' E., on the N-S center line of the SE 1/4 of section 10.

19.992 Point for the SE 1/16 section corner of section 10, at the intersection with the E-W center line of the SE 1/4 of section.

THE SUBDIVISION OF SECTION 10,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

SE 1/16 S 10
2007

Set a steel fence post alongside the aluminum post.

Corner is located on flat grassy area.

39.984 The center E 1/16 section corner of section 10.

From the S 1/16 section corner of sections 10 and 11.

N. 89°15.7' W., on the E-W center line of the SE 1/4 of section 10.

20.052 The SE 1/16 section corner of section 10.

40.104 The center S 1/16 section corner of section 10.

N. 89°15.9' W., on the E-W center line of the SW 1/4 of section 10.

40.021 The S 1/16 section corner of sections 9 and 10.

The Subdivision of Section 11,
Township 3 South, Range 8 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of section 11 only.

N. 0°16.7' W., on the N-S center line of section 11.

20.285 Point for the center S 1/16 section corner of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, with aluminum cap marked:

C
S 1/16 | S 11
C
2007

Set a steel fence post alongside the aluminum post.

Corner is located on a rocky, west facing slope.

40.570 Point for the center 1/4 section corner of section 11 at the intersection with the E-W center line of section.

THE SUBDIVISION OF SECTION 11,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

T 3 S R 8 W
C 1/4 S 11
2007

Set a steel fence post alongside the aluminum post.

Corner is located on a rocky, SW facing slope.

60.564 Point for the center N 1/16 section corner of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

C
N 1/16 | S 11
C
2007

Raise a mound of stone, 3 ft. base, 1 ft. high, north of corner.

Set a steel fence post alongside the aluminum post.

Corner is located on steep, rocky, north facing slope.

80.558 The 1/4 section corner of sections 2 and 11.

From the 1/4 section corner of sections 11 and 12.

N. 89°26.8' W., on the E-W center line of section 11.

19.816 Point for the center E 1/16 section corner of section 11.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 25 inches in the ground, with aluminum cap marked:

E 1/16
C ————— C
S 11
2007

Set a steel fence post alongside the aluminum post.

Corner is located on a gentle, NE facing slope surrounded by burnt cedar trees.

39.632 The center 1/4 section corner of section 11.

79.670 The 1/4 section corner of sections 10 and 11.

THE SUBDIVISION OF SECTION 11,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

From the center E 1/16 section corner of section 11.

N. 0°02.5' W., on the N-S center line of the NE 1/4 of section 11.

19.990 Point for the NE 1/16 section corner of section 11, at the intersection with the E-W center line of the NE 1/4 of section.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

NE 1/16 S 11
2007

Set a steel fence post alongside the aluminum post.

Corner is located on an east facing slope, approximately 60 links west of a drainage, course north.

39.980 The point for the E 1/16 section corner of sections 2 and 11.

From the point for the N 1/16 section corner of sections 11 and 12.

N. 89°26.0' W., on the E-W center line of the NE 1/4 of section 11.

19.897 The NE 1/16 section corner of section 11.

39.794 The center N 1/16 section corner of section 11.

From the E 1/16 section corner of section 11 only.

N. 0°01.2' E., on the N-S center line of the SE 1/4 of section 11.

20.143 Point for the SE 1/16 section corner of section 11, at the intersection with the E-W center line of the SE 1/4 of section.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

SE 1/16 S 11
2007

40.286 The center E 1/16 section corner of section 11.

From the S 1/16 section corner of sections 11 and 12.

N. 89°51.3' W., on the E-W center line of the SE 1/4 of section

THE SUBDIVISION OF SECTION 11,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

11.

19.711 The SE 1/16 section corner of section 11.

39.422 The center S 1/16 section corner of section 11.

From the center N 1/16 section corner of section 11.

N. 89°26.2' W., on the E-W center line of the NW 1/4 of section 11.

39.998 The N 1/16 section corner of sections 10 and 11.

The Subdivision of Section 13,
Township 3 South, Range 8 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of section 13 only.

N. 0°12.5' E., on the N-S center line of section 13.

39.755 Point for the center 1/4 section corner of section 13 at the intersection with the E-W center line of section.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 24 inches in the ground, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

T 3 S R 8 W
C 1/4 S 13
2008

Corner is located on NW facing slope in sparse cedars.

59.526 Point for the center N 1/16 section corner of section 13.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

C
|
N 1/16 | S 13
|
C
2008

Set a steel fence post along the west side of the aluminum post.

Corner is located on south facing slope.

79.297 The 1/4 section corner of sections 12 and 13.

From the 1/4 section corner of sections 13 and 18 on the east

THE SUBDIVISION OF SECTION 13,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

boundary of the township, hereinbefore described.

N. 89°38.5' W., on the E-W center line of section 13.

20.140 Point for the center E 1/16 section corner of section 13.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 22 inches in the ground, in a mound of stone, 2 ft. base, to top of aluminum cap marked:

E 1/16
C ————— C
S 13
2008

Corner is located on west facing slope surrounded by cedar trees.

40.280 The center 1/4 section corner of section 13.

60.129 Point for the center W 1/16 section corner of section 13.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

W 1/16
C ————— C
S 13
2008

Set a steel fence post alongside the aluminum post.

79.978 The 1/4 section corner of sections 13 and 14.

From the center E 1/16 section corner of section 13.

N. 0°02.2' E., on the N-S center line of the NE 1/4 of section 13.

19.880 Point for the NE 1/16 section corner of section 13, at the intersection with the E-W center line of the NE 1/4 of section.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

NE 1/16 S 13
2008

Set a steel fence post alongside the aluminum post.

39.760 The E 1/16 section corner of sections 12 and 13.

From the N 1/16 section corner of sections 13 and 18 on the east

THE SUBDIVISION OF SECTION 13,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

boundary of the township, hereinbefore described.

N. 89°57.1' W., on the E-W center line of the NE 1/4 of section 13.

20.079 The NE 1/16 section corner of section 13.

40.158 The center N 1/16 section corner of section 13.

From the center W 1/16 section corner of section 13.

N. 0°06.2' E., on the N-S center line of the NW 1/4 of section 13.

19.885 Point for the NW 1/16 section corner of section 13, at the intersection with the E-W center line of the NW 1/4 of section.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

NW 1/16 S 13
2008

Set a steel fence post alongside the aluminum post.

39.770 The point for the W 1/16 section corner of sections 12 and 13.

From the center N 1/16 section corner of section 13.

N. 89°18.9' W., on the E-W center line of the NW 1/4 of section 13.

19.885 The NW 1/16 section corner of section 13.

39.770 The N 1/16 section corner of sections 13 and 14.

The Subdivision of Section 15,
Township 3 South, Range 8 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 15 and 22.

N. 1°41.3' W., on the N-S center line of section 15.

19.844 Point for the center S 1/16 section corner of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 15,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

$$\begin{array}{c} C \\ S \ 1/16 \quad | \quad S \ 15 \\ C \\ 2007 \end{array}$$

Set a steel fence post alongside the aluminum post.

- 39.688 Point for the center 1/4 section corner of section 15 at the intersection with the E-W center line of section.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} T \ 3 \ S \ R \ 8 \ W \\ C \ 1/4 \ S \ 15 \\ 2007 \end{array}$$

Set a steel fence post alongside the aluminum post.

- 79.742 The true point for the 1/4 section corner of sections 10 and 15.
-

From the 1/4 section corner of section 15 only.

N. 89°14.3' W., on the E-W center line of section 15.

- 38.666 The center 1/4 section corner of section 15.

- 59.436 Point for the center W 1/16 section corner of section 15.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

$$\begin{array}{c} W \ 1/16 \\ C \text{-----} C \\ S \ 15 \\ 2007 \end{array}$$

Set a steel fence post alongside the aluminum post.

- 80.206 The 1/4 section corner of sections 15 and 16.
-

From the W 1/16 section corner of sections 15 and 22.

N. 0°38.1' W., on the N-S center line of the SW 1/4 of section 15.

- 19.927 Point for the SW 1/16 section corner of section 15, at the intersection with the E-W center line of the SW 1/4 of section.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 29 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 15,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

SW 1/16 S 15
2007

Set a steel fence post alongside the aluminum post.

39.854 The center W 1/16 section corner of section 15.

From the center S 1/16 section corner of section 15.

N. 89°29.9' W., on the E-W center line of the SW 1/4 of section 15.

21.134 The SW 1/16 section corner of section 15.

42.268 The S 1/16 section corner of sections 15 and 16.

The Subdivision of Section 25,
Township 3 South, Range 8 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 25 and 36.

N. 0°15.1' E., on the N-S center line of section 25.

39.763 Point for the center 1/4 section corner of section 25 at the intersection with the E-W center line of section, falls in a gulch, drains west, where it is unsuitable for monumentation; not monumented.

79.155 The 1/4 section corner of section 25 only.

From the 1/4 section corner of sections 25 and 30 on the east boundary of the township, hereinbefore described.

N. 89°34.7' W., on the E-W center line of section 25.

40.111 The point for the center 1/4 section corner of section 25.

80.090 The 1/4 section corner of sections 25 and 26.

The Subdivision of Section 26,
Township 3 South, Range 8 West, Salt Lake Meridian, Utah.

From the 1/4 section corner of sections 26 and 35.

N. 0°31.5' E., on the N-S center line of section 26.

20.020 Point for the center S 1/16 section corner of section 26, not monumented.

THE SUBDIVISION OF SECTION 26,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

- 40.040** Point for the center 1/4 section corner of section 26 at the intersection with the E-W center line of section.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 26 inches in the ground, with aluminum cap marked:

T 3 S R 8 W
C 1/4 S 26
2007

Set a steel fence post alongside the aluminum post.

- 80.035** The 1/4 section corner of section 26 only.
-

From the 1/4 section corner of sections 25 and 26.

S. 89°40.7' W., on the E-W center line of section 26.

- 19.944** Point for the center E 1/16 section corner of section 26.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 28 inches in the ground, with aluminum cap marked:

E 1/16
C ————— C
S 26
2007

Set a steel fence post alongside the aluminum post.

- 39.888** The center 1/4 section corner of section 26.

- 80.025** The 1/4 section corner of sections 26 and 27.
-

From the center E 1/16 section corner of section 26.

N. 0°27.0' E., on the N-S center line of the NE 1/4 of section 26.

- 40.000** The E 1/16 section corner of section 26 only.
-

From the point for the E 1/16 section corner of sections 26 and 35.

N. 0°27.0' E., on the N-S center line of the SE 1/4 of section 26.

- 20.011** Point for the SE 1/16 section corner of section 26, at the intersection with the E-W center line of the SE 1/4 of section.

Set an aluminum post, 30 inches long, 2 1/2 inches diameter, 27 inches in the ground, with aluminum cap marked:

THE SUBDIVISION OF SECTION 26,
TOWNSHIP 3 SOUTH, RANGE 8 WEST, SALT LAKE MERIDIAN, UTAH.

CHAINS

SE 1/16 S 26
2007

Set a steel fence post alongside the aluminum post.

40.022 The center E 1/16 section corner of section 26.

From the S 1/16 section corner of sections 25 and 26.

S. 89°39.4' W., on the E-W center line of the SE 1/4 of section 26.

19.971 The SE 1/16 section corner of section 26.

39.942 The point for the center S 1/16 section corner of section 26.

Survey of the Iosepa Cemetery in Section 22

From the NE corner of the Iosepa Cemetery, at the corner of fences extending S. 5°00.5' W., and N. 88°48.3' W.

N. 88°48.3' W., along the north boundary of the Cemetery.

0.064 Intersect the N-S centerline of section 22.

3.258 The NW corner of the Iosepa Cemetery, at the corner of fences extending S. 4°09.3' E., and S. 88°48.3' E.

S. 4°09.3' E., along the west boundary of the Cemetery.

2.633 The SW corner of the Iosepa Cemetery, at the corner of fences extending N. 4°09.3' W., and S. 86°37.1' E.

S. 86°37.1' E., along the south boundary of the Cemetery.

2.833 The SE corner of the Iosepa Cemetery, at the corner of fences extending N. 5°00.5' E., and N. 86°37.1' W.

N. 5°00.5' E., along the east boundary of the Cemetery.

1.381 Intersect the N-S centerline of section 22.

2.735 The NE corner of the Iosepa Cemetery, and the point of beginning.

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FIELD ASSISTANTS

Name	Capacity
Calvert C. Norton	Survey Technician
Glen B. Hatch	Cadastral Surveyor
Adrian M. Kurip	Survey Technician
R. Keith Batty	Survey Technician

CERTIFICATE OF SURVEY

We, *Ronald K. Baugh, Supervisory Cadastral Surveyor, and Daniel T. Gillins, Survey Technician*, hereby certify upon honor, that in pursuance of special instructions bearing the date of the *6th day of November, 2006*, we have executed a *dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines, a corrective resurvey of a portion of the subdivision lines and subdivision of section 22, a survey of a portion of the subdivisional lines, and the subdivision of sections 10, 11, 13, 15, 25, and 26 in Township 3 South, Range 8 West,*

of the *Salt Lake* Meridian, in the State of *Utah*, which are represented in the foregoing field notes as having been executed by us and under our direction; and that said survey has been made in strict conformity with said special instructions, the Manual of Instructions of the Survey of the Public Lands of the United States, and in specific manner described in the foregoing field notes.

Jan. 28, 2011
Date

Ronald K. Baugh
Supervisory Cadastral Surveyor

January 28, 2011
Date

Daniel T. Gillins
Survey Technician

CERTIFICATE OF APPROVAL

BUREAU OF LAND MANAGEMENT
Salt Lake City, Utah

The following field notes of the *dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines, the corrective resurvey of a portion of the subdivisional lines and the subdivision of section 22, the survey of a portion of the subdivisional lines, and the subdivision of sections 10, 11, 13, 15, 25, and 26 in Township 3 South, Range 8 West, Salt Lake Meridian, Utah,*

Executed by *Ronald K. Baugh, Supervisory Cadastral Surveyor, and Daniel T. Gillins, Survey Technician,*, having been critically examined and found correct, are hereby approved.

March 21, 2011
Date

Daniel W. Webb
(Chief Cadastral Surveyor for Utah)

[illegible]